

8-Line Professional Carrier-Grade IP Phone **GRP2634**

Part of the GRP series of Carrier-Grade IP Phones, the GRP2634 is a professional 8-line model designed with zero-touch provisioning for mass deployment and easy management. It features a sleek design and a suite of next-generation features including: 5-way voice conferencing to maximize productivity, integrated PoE & Wi-Fi 6, full HD audio on both the speaker and handset to allow users to communicate with the utmost clarity, EHS support for Plantronics headsets and USB to support Grandstream's GUV Series Headsets. The GRP series includes carrier-grade security features to provide enterprise-level security, including secure boot, dual firmware images and encrypted data storage. For cloud provisioning and centralized management, the GRP2634 is supported by Grandstream's Device Management System (GDMS), which provides a centralized interface to configure, provision, manage and monitor deployments of Grandstream endpoints. With 32 Virtual Multi-Purpose Keys (VPK) and 10 Multi-Purpose Keys (MPK), the GRP2634 is the perfect choice for busy professionals and receptionists who need to manage high call volumes, with advanced functionality. Designed for easy deployment by enterprises, service providers and other high-volume markets, the GRP2634 offers an easy-to-use and easy-to-deploy voice endpoint.



8 lines, 12 SIP accounts



Supported by GDMS which provides a centralized interface to configure, provision, manage and monitor Grandstream devices



RJ9 headset jack allowing EHS with Plantronics headsets, and integrated USB Headset support



Full-duplex speakerphone with HD audio to maximize audio quality and clarity



Equipped with noise shield technology to minimize background noise



Dual switched autosensing 10/100/1000 Mbps Gigabit Ethernet ports with integrated PoE



Supports 5-way audio conferencing for easy conference calls



Enterprise-level protection including secure boot, dual firmware images, and encrypted data storage



Swappable faceplate to allow for easy logo customization



Integrated dual-band (2.4GHz and 5GHz) Wi-Fi 6 (802.11a/b/g/n/ac/ax) - hardware version 5.0 and above

Protocols/Standards	SIP RFC3261, TCP/IP/UDP, RTP/RTCP, HTTP/HTTPS, ARP, ICMP, DNS(A record, SRV, NAPTR), DHCP, PPPoE, TELNET, TFTP, NTP, STUN, SIMPLE, LLDP, LDAP, TR-069, 802.1x, TLS, SRTP, IPV6
Network Interfaces	Dual switched auto-sensing 10/100/1000 Mbps Gigabit Ethernet ports with integrated PoE
Graphic Display	2.8 inch (320x240) TFT color LCD
Wi-Fi	Integrated dual-band (2.4GHz and 5GHz) Wi-Fi 6 (802.11a/b/g/n/ac/ax) - hardware version 5.0 and above
Bluetooth	Yes, integrated
Feature Keys	8 line keys with up to 12 SIP accounts, 10 MPK extension keys with paper slot, 4 XML programmable context sensitive softkeys, 5 navigation/menu keys, 9 dedicated function keys for: MESSAGE(with LED indicator), TRANSFER, HEADSET, MUTE, SEND/REDIAL, SPEAKERPHONE, VOL+, VOL-
Auxiliary Port	RJ9 headset jack allowing EHS with Plantronics headsets, USB to support Grandstream's GUV Series headsets and other USB headsets
Voice Codecs and Capabilities	Support for G7.29A/B, G.711μ/a-law, G.726, G.722(wide-band), G723, iLBC, OPUS, inband and out-of-band DTMF(in audio, RFC2833, SIP INFO)
Telephony Features	Hold, transfer, forward, 5-way conference, call park, call pickup, shared-call-appearance(SCA)/bridged-line-appearance(BLA), downloadable phonebook(XML, LDAP, up to 2000 items), call waiting, call log(up to 2000 records), XML customization of screen, off-hook auto dial, auto answer, click-to-dial, flexible dial plan, hot-desking, personalized music ringtones and music on hold, server redundancy and fail-over
HD Audio	Yes, HD handset and speakerphone with support for wideband audio. Dual Microphone.
Extension Module	No
Base Stand	Yes, 2 angle positions available, Wall Mountable (Wall Mount *sold separately)
QoS	Layer 2 QoS (802.1Q, 802.1P), 802.11e (WMM) and Layer 3 (ToS, DiffServ, MPLS) QoS
Security	User and administrator level passwords, MD5 and MD5-sess based authentication, 256-bit AES encrypted configuration file, SRTP, TLS, 802.1x media access control, secure boot.
Multi-language	English, German, Italian, French, Spanish, Portuguese, Russian, Croatian, Chinese, Korean, Japanese and more
Upgrade/Provisioning	Firmware upgrade via FTP/TFTP/TFTPS/HTTP/HTTPS, mass provisioning using GDMS/TR-069 or AES encrypted XML configuration file.
Upgrade/Provisioning Power & Green Energy Efficiency	
	TR-069 or AES encrypted XML configuration file. Universal power adapter included: Input:100-240V; Output: +12V, 1A; Integrated Power-over-Ethernet (802.3af) IEEE 802.3az Energy-Efficient Ethernet Max power consumption 9.5W (power adapter) or 10.8W (PoE) Operation: 0°C to 40°C
Power & Green Energy Efficiency	TR-069 or AES encrypted XML configuration file. Universal power adapter included: Input:100-240V; Output: +12V, 1A; Integrated Power-over-Ethernet (802.3af) IEEE 802.3az Energy-Efficient Ethernet Max power consumption 9.5W (power adapter) or 10.8W (PoE) Operation: 0°C to 40°C Storage: -10°C to 60°C
Power & Green Energy Efficiency Temperature and Humidity	TR-069 or AES encrypted XML configuration file. Universal power adapter included: Input:100-240V; Output: +12V, 1A; Integrated Power-over-Ethernet (802.3af) IEEE 802.3az Energy-Efficient Ethernet Max power consumption 9.5W (power adapter) or 10.8W (PoE) Operation: 0°C to 40°C Storage: -10°C to 60°C Humidity: 10% to 90% Non-condensing GRP2634 phone, handset with cord, phone stand, 12V power adapter, network cable,